

Pneumatic Actuation Ordering Information

| Size | Material | Code | Series | Action | Code | Options | Code |
|------|---|------|----------|---------------|------|----------------------------|--------------------|
| A | Cataphoresis and Rilsan Coated Aluminum | | 79P/79PA | Double Acting | | No Solenoid | N |
| B | | | | Single Acting | S | NEMA 4 Solenoid | W115A [115 VAC] |
| B5 | Glass-filled Polyamide | P | | | | NEMA 4 Dbl Limit Switch | M2 |
| C | 316 SS | S | | | | 3-15 psi Positioner | C2 |
| C5 | | | | | | 4-20 mA Positioner | C1 |
| D | | | | | | | |
| D5 | | | | | | | |
| E | | | | | | | |

Examples:
BP79PSN:
 B Size, Glass-filled Polyamide, Series 79P, Single Acting, No Options
F79PW115A:
 F Size, Aluminum, Series 79P, Double Acting, with 115 VAC NEMA 4 Solenoid

PA-Series

| Air to Air | | Air to Spring | |
|------------|----------|---------------|----------|
| Model No. | Item No. | Model | Item No. |
| A79PAN | 2441001 | A79PASN | 2442001 |
| B79PAN | 2441000 | B79PASN | 2442000 |
| B579PAN | 2441005 | B579PASN | 2442005 |
| C79PAN | 2441010 | C79PASN | 2442010 |
| C579PAN | 2441015 | C579PASN | 2442015 |
| D79PAN | 2441020 | D79PASN | 2442020 |
| D579PAN | 2441025 | D579PASN | 2442025 |
| E79PAN | 2441030 | E79PASN | 2442030 |

P-Series Cataphoresis and Rilsan Coated Aluminum Body

| Air to Air | | Air to Spring | |
|------------|----------|---------------|----------|
| Model No. | Item No. | Model | Item No. |
| F79PAN | 2355000 | F79PASN | 2364000 |
| G79PAN | 2358000 | G79PASN | 2368000 |
| L79PAN | 2358001 | L79PASN | 2368001 |
| M79PAN | 2358002 | M79PASN | 2368002 |

316 Stainless Steel Body

| Air to Air | | Air to Spring | |
|------------|----------|---------------|----------|
| Model No. | Item No. | Model | Item No. |
| BS79PN | 2444014 | BS79PSN | 2445014 |
| CS79PN | 2444017 | CS79PSN | 2445017 |
| DS79PN | 2444022 | DS79PSN | 2445022 |
| ES79PN | 2444030 | ES79PSN | 2445030 |
| FS79PN | 2444040 | ES79PSN | 2445040 |

Glass-filled Polyamide

| Air to Air | | Air to Spring | |
|------------|----------|---------------|----------|
| Model No. | Item No. | Model | Item No. |
| AP79PN | 2343011 | AP79PSN | 2344011 |
| BP79PN | 2343014 | BP79PSN | 2344014 |
| CP79PN | 2343017 | CP79PSN | 2344017 |
| DP79PN | 2343022 | DP79PSN | 2344022 |

Option Series 79

| Options | 79 Item # |
|---|-----------|
| Positioners | |
| PST-202 SMART 4-20mA | |
| Air-to-Air (Standard with Transmitter) | 2415420 |
| Air-to-Spring (Standard with Transmitter) | 2415420 |
| Positioner & Transmitter with HART Protocol | 2415425 |
| PST-101 3-15 PSI | |
| Air-to-Air | 2414315 |
| Air-to-Spring | 2414315 |
| PST-101 3-15 PSI Positioner Options | |
| 2 X SPDT Mechanical Switches | 2414320 |
| AS-I Bus Options | |
| A79-E79 Air-Air, Air-Spring | 2407010 |
| F79-G79 Air-Air, Air-Spring | 2407040 |
| Limit Switches | |
| Type 4, Double (2-SPDT) | 2403779 |
| Type 7, Double (2-SPDT) | 2403780 |
| Inductive Sensor (2-SPDT) | 2408000 |
| I Switch | |
| NEMA 4 Double (2-SPDT) | 2403785 |
| Solenoids | |
| Type 4, Plastic, 120 VAC | 2401779 |
| Type 7, Plastic, 120 VAC | 2401780 |
| P-Series Solenoid, IP65 | 2401783 |
| Voltages | |
| 12 VDC | 2415749 |
| 24 VDC | 2415750 |
| 12 VAC | 2415751 |
| 24 VAC | 2415752 |
| 220 VAC | 2415753 |
| Camstops | |
| BP79P | 2221000 |
| CP79P | 2222000 |
| DP79P | 2223000 |
| E79P | 2224000 |
| F79P | 2225000 |
| G79P | 2439000 |
| Filter Regulator with Gauge | 2123000 |

De-Clutchable Manual Override

| Description | Part Number |
|----------------------------------|-------------|
| B79PA Declutch Man O/R-RD315 | 2219000 |
| B5-C579PA Declutch Man O/R-RD315 | 2219010 |
| D79PA Declutch Man O/R-RD320 | 2219020 |
| D579PA Declutch Man O/R-RD330 | 2219030 |
| E79PA Declutch Man O/R-RD330 | 2219030 |
| F79P Declutch Man O/R-RD345 | 2219040 |
| G79P Declutch Man O/R-RD350 | 2219050 |
| L79P Declutch Man O/R-RD360 | 2219060 |
| M79P Declutch Man O/R-RD370 | 2219070 |

Electric Actuation Ordering Information

| Size | Series | Options | | Enclosure | Code | Output Torque |
|------|--------|------------------------|-----|-------------------|------|----------------|
| S | 92 | 1 Extra Limit Switch | M1 | General Locations | W | 400 in./lbs. |
| A | 92 | 2 Extra Limit Switches | M2 | General Locations | W | 700 in./lbs. |
| B | 92 | Heater & Thermostat | HT | General Locations | W | 1100 in./lbs. |
| C | 92 | Feedback Pot | P | General Locations | W | 2000 in./lbs. |
| | | Center Off | CO | | | |
| A | 94 | 2 Wire Control | 2WC | | | |
| B | 94 | Failsafe Battery Pack | FS | General Locations | W | 150 in./lbs. |
| | | Positioner | C1 | General Locations | W | 300 in./lbs. |
| | | RHM Module | RHM | | | |
| | | Transmitter | C3 | | | |
| | | Hazardous Locations | XW | | | |
| | | | | General Locations | W | 1320 in./lbs. |
| | | | | General Locations | W | 1740 in./lbs. |
| | | | | General Locations | W | 2580 in./lbs. |
| | | | | General Locations | W | 4320 in./lbs. |
| | | | | General Locations | W | 5220 in./lbs. |
| | | | | General Locations | W | 6960 in./lbs. |
| | | | | General Locations | W | 10440 in./lbs. |
| | | | | General Locations | W | 17400 in./lbs. |
| | | | | General Locations | W | 26040 in./lbs. |

Examples:

A92RHMWX:

A Size, Series 92 with RHM module hazardous locations

B94C1W:

B Size, Series 94, positioner, general location

10-15PM2HTW

10-15P Size, Series 10P, two extra limit switches, heater and thermostat, general locations

Series 92 Actuators

| General Locations (120 VAC) | | |
|-----------------------------|---------------|-------------|
| Model | Output Torque | Part Number |
| S92W | 400 in./lbs. | 2172000 |
| A92W | 700 in./lbs | 2173000 |
| B92BRW | 1100 in./lbs | 2174000 |
| C92BRW | 2000 in./lbs | 2175000 |
| General Locations (12 VDC) | | |
| Model | Output Torque | Part Number |
| S92W | 400 in./lbs | 2172001 |
| A92W | 700 in./lbs | 2173001 |
| B92W | 1100 in./lbs | 2174001 |
| C92W | 2000 in./lbs | 2175001 |
| C92GW | 5000 in./lbs | 2175071 |
| General Locations (24 VDC) | | |
| Model | Output Torque | Part Number |
| S92W | 400 in./lbs | 2172002 |
| A92W | 700 in./lbs | 2173002 |
| B92W | 1100 in./lbs | 2174002 |
| C92W | 2000 in./lbs | 2175002 |
| C92GW | 5000 in./lbs | 2175072 |
| General Locations (12 VAC) | | |
| Model | Output Torque | Part Number |
| S92W | 400 in./lbs | 2172003 |
| A92W | 700 in./lbs | 2173003 |
| B92W | 1100 in./lbs | 2174003 |
| C92W | 2000 in./lbs | 2175003 |
| General Locations (24 VAC) | | |
| Model | Output Torque | Part Number |
| S92W | 400 in./lbs | 2172004 |
| A92W | 700 in./lbs | 2173004 |
| B92W | 1100 in./lbs | 2174004 |
| C92W | 2000 in./lbs | 2175004 |
| General Locations (220 VAC) | | |
| Model | Output Torque | Part Number |
| S92W | 400 in./lbs | 2172005 |
| A92W | 700 in./lbs | 2173005 |
| B92BRW | 1100 in./lbs | 2174005 |
| C92BRW | 2000 in./lbs | 2175005 |

| Hazardous Locations (120 VAC) | | |
|-------------------------------|---------------|-------------|
| Model | Output Torque | Part Number |
| S92XW | 400 in./lbs | 2172500 |
| A92XW | 700 in./lbs | 2173500 |
| B92BRXW | 1100 in./lbs | 2174500 |
| C92BRXW | 2000 in./lbs | 2175500 |
| Hazardous Locations (12 VDC) | | |
| Model | Output Torque | Part Number |
| S92XW | 400 in./lbs | 2172501 |
| A92XW | 700 in./lbs | 2173501 |
| B92XW | 1100 in./lbs | 2174501 |
| C92XW | 2000 in./lbs | 2175501 |
| C92GXW | 5000 in./lbs | 2175571 |
| Hazardous Locations (24 VDC) | | |
| Model | Output Torque | Part Number |
| S92XW | 400 in./lbs | 2172502 |
| A92XW | 700 in./lbs | 2173502 |
| B92XW | 1100 in./lbs | 2174502 |
| C92XW | 2000 in./lbs | 2175502 |
| C92GXW | 5000 in./lbs | 2175572 |
| Hazardous Locations (220 VAC) | | |
| Model | Output Torque | Part Number |
| S92XW | 400 in./lbs | 2172505 |
| A92XW | 700 in./lbs | 2173505 |
| B92BRXW | 1100 in./lbs | 2174505 |
| C92BRXW | 2000 in./lbs | 2175505 |

Series 94 Actuators

| General Locations (120 VAC) | | |
|-----------------------------|---------------|-------------|
| Model | Output Torque | Part Number |
| A94W | 150 in./lbs | 2070800 |
| B94W | 300 in./lbs | 2070900 |
| General Locations (12 VDC) | | |
| Model | Output Torque | Part Number |
| A94W | 150 in./lbs | 2070801 |
| B94W | 300 in./lbs | 2070901 |
| General Locations (24 VDC) | | |
| Model | Output Torque | Part Number |
| A94W | 150 in./lbs | 2070802 |
| B94W | 300 in./lbs | 2070902 |
| General Locations (12 VAC) | | |
| Model | Output Torque | Part Number |
| A94W | 150 in./lbs | 2070803 |
| B94W | 300 in./lbs | 2070903 |
| General Locations (24 VAC) | | |
| Model | Output Torque | Part Number |
| A94W | 150 in./lbs | 2070804 |
| B94W | 300 in./lbs | 2070904 |
| General Locations (220 VAC) | | |
| Model | Output Torque | Part Number |
| A94W | 150 in./lbs | 2070805 |
| B94W | 300 in./lbs | 2070905 |

Series 92 and 94 Options

| | 92 Item # | 94 Item # |
|----------------------------------|-----------|-----------|
| Double Extra Limit Switch | 2126002 | 2126004 |
| Heater & Thermostat | 2127001 | 2127001 |
| RHM | 2133001 | 2132002 |
| UL1203 Explosion-Proof Enclosure | 2130900 | N/A |
| Feedback Potentiometer | 2129001 | 2129003 |
| 4-20 mA Positioner | 2130810 | 2130812 |
| 4-20 mA Transmitter | 2130813 | 2130813 |
| ModBus Card | 2130821 | 2130821 |
| Cycle Length Control | 2131001 | 2131003 |
| Mechanical Brake | 2136001 | 2136001 |
| Center Off Switch | 2132001 | 2132003 |
| 2-Wire Control | 2102001 | 2102008 |
| Protek Failsafe Battery Pack | 2154000 | 2154001 |
| LL-200C Local/Remote Station (1) | 2190000 | 2190000 |
| PK-100 Local/Remote Station (2) | 2190001 | 2190001 |
| Voltages: | | |
| 12 VDC | 2135749 | 2135749 |
| 24 VDC | 2135750 | 2135750 |
| 12 VAC | 2135751 | 2135751 |
| 24 VAC | 2135752 | 2135752 |
| 220VAC | 2135753 | 2135753 |

(1) For open/close 120vac units only

(2) For 120/230vac modulating units with DHC Positioner

Series 10P Actuators

| General Locations (120 VAC) | | |
|-----------------------------|---------------|-------------|
| Model | Output Torque | Part Number |
| 10-15P | 1320 | 204902 |
| 10-20P | 1740 | 204909 |
| 10-30P | 2580 | 204903 |
| 10-50P | 4320 | 204904 |
| 10-60P | 5220 | 204910 |
| 10-80P | 6960 | 204905 |
| 10-120P | 10440 | 204906 |
| 10-200P | 17400 | 204907 |
| 10-300P | 26040 | 204908 |
| General Locations (230 VAC) | | |
| Model | Output Torque | Part Number |
| 10-15P | 1320 | 2049992 |
| 10-20P | 1740 | 2049999 |
| 10-30P | 2580 | 2049993 |
| 10-50P | 4320 | 2049994 |
| 10-60P | 5220 | 2049990 |
| 10-80P | 6960 | 2049995 |
| 10-120P | 10440 | 2049996 |
| 10-200P | 17400 | 2049997 |
| 10-300P | 26040 | 2049998 |

Series 10P Actuators Options

| | |
|----------------------------------|---------|
| Feedback Potentiometer | 2129001 |
| 4-20 mA Positioner | 2130822 |
| 4-20 mA Transmitter | 2130813 |
| ModBus Card | 2130821 |
| Cycle Length Control | 2131001 |
| 2-Wire Control | 2102001 |
| LL-200C Local/Remote Station (1) | 2190000 |
| PK-100 Local/Remote Station (2) | 2190001 |

(1) For open/close 120vac units only

(2) For 120/230vac modulating units with DHC Positioner