



4a	RING	2	STAINLESS STEEL 304	Used for CPVC Body. Threaded End : 1/2" ~ 1"
14	HANDLE	1	ABS	
13	STOP RING	2	PVDF	Used for Flanged End
12	O-RING (E)	1	EPDM,FKM, etc.	
11	O-RING (D)	1	EPDM,FKM, etc.	
10	O-RING (C)	2	EPDM,FKM, etc.	
9	O-RING (B)	1	EPDM,FKM, etc.	
8	O-RING (A)	2	EPDM,FKM, etc.	
7	SEAT	2	PTFE	
6	STEM	1	PVC,CPVC,PP,PVDF	
5	UNION NUT	2	PVC,CPVC,PP,PVDF	
4e	END CONNECTOR (SPIGOT)	2	PP,PVDF	BUTT END
4d	END CONNECTOR (THREADED)	2	PVC,CPVC,PP,PVDF	
4c	END CONNECTOR (SOCKET)	2	PVC,CPVC,PP,PVDF	
4b	END CONNECTOR (FLANGED)	2	PVC,CPVC,PP,PVDF	
3	CARRIER	1	PVC,CPVC,PP,PVDF	
2	BALL	1	PVC,CPVC,PP,PVDF	
1	BODY	1	PVC,CPVC,PP,PVDF	
No.	DESCRIPTION	No.REQ'D	MATERIAL	REMARKS

THIS DRAWING AND ALL INFORMATION HEREON IS THE PROPERTY OF ASAHI/AMERICA. ANY COPYING, REPRODUCTION OR UNAUTHORIZED USE IS FORBIDDEN WITHOUT WRITTEN CONSENT.

ASAHI/AMERICA

ISO 9001 CERTIFIED

35 GREEN STREET, P.O. BOX 653, MALDEN, MA.



BALL VALVE TYPE21
EXPLODED VIEW
1/2" THRU. 2"

	NAME	DATE
DR	KENICHI MIYAZAKI	8/26/02
APPD	DAVE HURLEY	8/26/02
PROD	LEO LESTER	8/26/02
WO#/SO#		
FILE		

SIZE	A	DWG. NO.	0097BV	REV	B
SCALE	NTS		SHEET 1 OF 1		

FOR REFERENCE ONLY
ASAHI/AMERICA